

## Centrifugal Tablock Wheel Series / 片齒系列

### Material / 材質:




- A : steel w / painting - 鐵
- G : galvanized - 鍍鋅板
- B : aluminum - 鋁
- S : stainless steel - 不鏽鋼



A. or R. or CW



B. or L. or CCW



### Single Wheel

### MULTI-BLADE IMPELLER

SIZE		BORE	KEYWAY	ROTATION	REMARK
(D) (mm)	(D) (inch)				
127	5	—	—	—	R,L
152	6	—	—	—	R,L
170	6.6	—	—	—	R,L
178	7	—	—	—	R,L
190	7.5	—	—	—	R,L
200	8	—	—	—	R,L
230	9	—	—	—	R,L
248	9.6	—	—	—	R,L
270	10.5	—	—	—	R,L
280	11	—	—	—	R,L
295	11.6	—	—	—	R,L
305	12	—	—	—	R,L
330	13	—	—	—	R,L
356	14	—	—	—	R,L
<b>380</b>	<b>15</b>	—	—	—	<b>R,L</b>
456	18	—	—	—	R,L
533	21	—	—	—	R,L
610	24	—	—	—	R,L
685	27	—	—	—	R,L
763	30	—	—	—	R,L

• 孔徑鍵槽各異，以IEC為準，可依客戶規格訂作

### Dual Wheel

- Above TABLOCK MULTI-BLADE IMPELLERS can be conjoined as double-inlet type (Hx2) indicated as C \* B-M impllers
- 片齒雙口M系列可由單一風輪組合而成，高度為單口的兩倍



A. or R. or CW



B. or L. or CCW

### Other Wheel Series



FFU



Backward curved type



Strong Type



一體成型